



## The M509T Touch screen scanning UV-Vis Spectrophotometer

### Main features

- Local control via Touch screen
- Basic modes Absorbance %T and Concentration
- Quantitative up to 8 standards can be used
- Wavelength scanning
- Kinetics for time coursing and reaction rates
- DNA/Protein Concentration & DNA purity are calculated
- 4 x 10mm cell changer included
- 4 x 10mm Glass cells included
- 2 x 10mm Quartz cells included
- Plastic Instrument cover included



### Technical Specifications of the M509T

Display	Touch screen
Light sources	Tungsten-Halogen and Deuterium
Monochromator	1200 lines/mm grating
Detectors	Silicon Photodiode
Wavelength Range	190- 1000nm
Wavelength Accuracy	± 0.8nm
Wavelength Repeatability	± 1 nm
Noise	< 0.001A @ 500nm 0A
Zero Drift	< 0.003A per hour after warm-up
Bandpass	2 nm
Stray Light	<0.1%T @ 220nm and 340 nm
Photometric Accuracy	0.5%
Photometric Range	-0.3to 3.0A, 0-200%T and -9999C and +9999C
Printer Interface	Bluetooth (optional)
Computer Interface	USB for PC control
Power Requirements	110/120V, 220/230V, 50/60 Hz, 135VA
Dimensions	510 x 420 x 210 packed 645 x 535 x 370
Weight	14Kg packed 17Kg

Email: [sales@camspec.eu](mailto:sales@camspec.eu)

Tel: +44 (0) 113 286 4536

[www.camspec.eu](http://www.camspec.eu)



### **PC Control**

The M509T has a USB output for the transfer of results to a PC or for PC control of the M509T. Comprehensive Camspec Application Software is available.

### **A selection of the many Cell compartment Accessories available**

**Test-tube holder (100mm) P/N 501-101**

**Adjustable micro-cell holder P/N 501-102**

**4 x 10mm manual cell changer P/N 501-114**

**4-cell holder for 5-50mm cells P/N 501-104**

**4-cell holder for 100mm cells P/N 501-103**

**100mm cylindrical cell holder P/N 501-106**

**Thermostatted single cell (requires water bath) P/N 508-105**

**Sipper, processor controlled P/N 508-121**

**Peltier system for 10mm cells, 15-40°C P/N 508-123**

**Peltier/Sipper system combined P/N 508-124**

**Calibration standards for wavelength, absorbance, stray light**



**Email: [sales@camspec.eu](mailto:sales@camspec.eu)**

**Tel: +44 (0) 113 286 4536**

**[www.camspec.eu](http://www.camspec.eu)**